

## ● 2 Ring Air-Blast Kwali Range



2 Ring Air-Blast Kwali Range

### Advantages:

- Suitable for Stir frying and Cooking all kinds of foods
- High efficiency - up to 60% time saving & gas & energy consumption
- Up to 60% cooler Working environment
- User friendly & safe operating system
- Premixed combustion and high temperature air-gas premixed technology
- Innovation of Hearth and Waste Heat Reuse Patented Technique Greatly Improve Utilization of Energy
- Innovation of Double Premix Chamber and and Used of Multiple Nozzle Technique to Increase the 7. Premix of Gas Combustion Speed
- Distributed of Double Solenoid Valve Control to Prevent Gas Leakage
- Modular Exchangeable Components for Easy Maintenance

### R & D in Singapore by:

Green Resources Energy Saving Technology  
Greensmart F&B Equipment Pte. Ltd.

### GREENSMART F&B EQUIPMENT PTE LTD

Blk 3016 Bedok North Ave 4, #06-26

Singapore 489947

Tel:6787 3873/8322 0048

Email: greenresources3013@gmail.com



**Feature:**

- SUS304 Food grade Stainless steel interior & exterior
- Auto Ignition system
- Adjustable firepower
- Excellent Heat Preservation
- Space Conservation - Can fit into any existing setup
- Environment friendly - Maximize of heat efficiency (95%), reduce carbon emission.
- Individual air blower for each wok

**Benefits:**

- Increase productivity
- Increase quality control
- Reduce operation cost
- Reduce manpower & reliance of skilled workers

**Product Specification**

<b>Product name</b>	2 Rings Air-Blast Kwali Range		
<b>Product Model</b>	GS-2R-ABKR-1250-850	GS-2R-ABKR-1350-850	GS-2R-ABKR-1450-850
<b>Main Control</b>	Dual System		
<b>Heating</b>	Gas Fired		
<b>Dimension (mm)</b>	L1250mm W850mm H800mm (+400mm)	L1350mm W850mm H800mm (+400mm)	L1450mm W850mm H800mm (+400mm)
<b>Gas Consumption Heat Load BTU/hr.</b>	30kw + 30kw (204728 BTUs/Hr.)		
<b>Type of Gas</b>	LPG / CG / LNG		
<b>Power Supply</b>	1 Phase 230 / 50hz		
<b>Electric Consumption</b>	280watt + 280watt		

